MINISTRY OF EXTERNAL AFFAIRS (GOVT. OF INDIA)

DISTRICT GENERAL HOSPITAL, DIKOYA SRI LANKA

Tender

for

Supply Installation Testing & Commissioning of Kitchen Equipment at District General Hospital, Dikoya, Sri Lanka

VOLUME - V

PRICE BID

March 2013



(Consultants & Engineers for Mega Hospitals & Laboratories) E - 6 (A), Sector - I, NOIDA (U.P.) - 201 301 (INDIA)

PHONE: 91-2542436, 2542440 FAX: 91-11-91-2542447

Tender No. HSCC/PUR/MEA-SRILANKA/2013

BILL OF QUANTITIES Part-I Package - Supply, installation & commissioning of Kitchen with 1 year Defect Laibility Period Unit Rate in Rs. Unit Rate in Rs. Amount in Rs. SLN Item Specifications Size/Unit Qty. (in words) Description (in Figure) (In Figure) Top of 16 swg S.S-304 sheet on MS Angle 25x25mm frame work duly rust proof painted on Structure made of S.S-304 1200x600x850+150 Work table square/Tubular pipe. Sink made of 14 swg S.S-304 on LHS/RHS and under shelf made of 18 swg S.S-304 sheet. with under shelf Vertical legs of S.S-304 round pipe of 16 swg. 1.5" dia with nylon adjustable feet. The top is fitted with stud welded and Sink bolts with the frame for sturdy and stronger grip. 2 Stock Pot Stove Top of 16 swg. S.S-304 Sheet on M.S Angle frame work duly rust proof painted on SS Tubular/ Square legs with 600x600x600 adjustable bullet feet for uneven floors. Fitted with United/Sarna make heavy duty burner with pilot lamps with individual control valves and heavy duty cast iron pan support. 3 Exhaust hood Entire exhaust is made of 20 swg.S.S-304 Sheet with S.S-304 baffle filters. Fitted with grease collection tray and hung 3000x1600x600 with metal fasteners Double walled glass wool Insulated all S.S-304 Sheet body. The outer Most is of 18swg S.S-304 Sheet body. Fitted with 80ltr. 2 heavy duty high pressure burner with pilot lamp & individual control valves. Fitted with water inlet & water outlet valve & strainer at the bottom level of the boiler also fitted with a Top opening lid with insulated handle. The entire boiler is mounted on heavy duty tubular legs. Also fitted with a heavy duty tilting gear to extract the boiled food. 5 Brazing Pan Double walled mineral wool insulated all S.S-304sheet body on heavy duty tubular legs with adjustable bullet feet. Fitted 80 ltr. 2 with heavy duty burner with pilot lamp with individual control needle valve. Fitted with tilting gear to extract contents (Tilting) after cooking & water inlet valve. Also fitted with top opening lid with insulated handle. 6 Exhaust Hood Lentire exhaust is made of 20 swg.S.S-304 Sheet with S.S-304 baffle filters. Fitted with grease collection tray and hung 2700x1200x500 Structure made of mild steel angle frame duly rust proof painted . Top of 12 mm mild steel, front Panel and under shelf 1500x600x850 7 Chapatti Plate 2 cum puffer 18swg S.S-304sheet, vertical legs of S.S-304 round pipe of 16swg, 1.5" diameter with nylon adjustable feet, Complete with CI perforated grill for puffing of chapattis, heavy duty high pressure RV burner pilot, individual control valves Indian Oil corporation approved Top made of 16swg S.S-304 sheet on MS Angle frame work with rust proof painted on S.S-304 square pipe 1200x4500x850 8 Chapatti 2 Rolling Table 25x25mm/Tubular legs frame work and under shelf made of 18swg S.S-304 sheet. Vertical legs of S.S-304 round pipe of 16 swg. 1.5" dia with nylon adjustable feet. Entire exhaust is made of 20 swg.S.S-304 Sheet with S.S-304 baffle filters. Fitted with grease collection tray and hung 1500x750x500 9 Exhaust hood 10 Wall Cabinet All covered and door of SS-304 with lock and two Shelves constructed of 18 swg S.S-304 sheet & supports constructed 900x450x600 4 11 Marble Top Top of Marble on MS Angle 25x25mm frame work duly rust proof painted on Structure made of S.S-304 900x600x850 2 square/Tubular pipe. Under shelf made of 18 swg S.S-304 sheet. Vertical legs of S.S-304 round pipe of 16 swg. 1.5" dia Table with nylon adjustable feet. The top is fitted with stud welded bolts with the frame for sturdy and stronger grip. Top of 16 swg S.S-304 sheet on MS Angle 25x25mm frame work duly rust proof painted on Structure made of S.S-304 1200x600x850 12 Work Table 2 vith sink square/Tubular pipe. Sink made of 14 swg S.S-304 on LHS/RHS and under shelf made of 18 swg S.S-304 sheet. Vertical legs of S.S-304 round pipe of 16 swg. 1.5" dia with nylon adjustable feet. The top is fitted with stud welded bolts with the frame for sturdy and stronger grip. 13 Dough Kneader Body completely constructed of heavy duty cast iron with gear box mounted on the top the mixing bowl of S.S-304 sheet 25 kg. 2 14 swg with S.S-304 arm to mix the dough and is operated electrically with heavy duty motor of 1 hp. Motor shall be S1 type of IS: 325 standard (Latest version) and of Kirloskar/NGEF/Siemens/ABB/GEC/ Crompton Greaves make. 14 SS stand for All S.S-304 sheet body to hold poly carbonate chopping boards-4Nos. 450x300x600 Chopping blocks with oards

					,
15		The continuous flow pulveriser is made of S.S-304 gravity hopper on S.S-304 covering on MS angle frame work duly rust proof painted on adjustable bullet feet. Also fitted with a heavy duty motor (Motor shall be of continuous duty S1 type of IS: 325 standard (Latest version) and of Kirloskar/NGEF/Siemens/ABB/ GEC/ Crompton Greaves make) and 5 blades of different sizes. The heavy duty machine can grind both dry and wet.		1	
16	Referigerator	Structure made of mild steel angle frame duly rust proof painted. Body completely constructed of S.S-304 sheet double walled insulated with puf, inner tank of 22 swg and outer of 20swg S.S-304 sheet the inner chamber will have 3 nos. Of wire mesh made removal shelf with height adjusters mounted on S.S-304 channels. The refrigerator will have 2 nos. S.S-304 double walled insulated 18 swg doors spring activated with locking arrangements. The refrigerator is mounted on four S.S-304 tubular legs with S.S-304 bullet adjustable feet. The compressor and condenser unit of Emerson/Techumshah/Kirloskar/Equivalent make with Automatic temperature controller and temp. Indicator.	1200x750x2000	1	
	Landing Table with glass Rack with Garbage chute	The marine edged top made of 16 swg SS: 304 sheet on MS Angle frame work, duly rust proof painted & stud welded for stronger grip and cross bracing of 18 swg SS: 304 sheet. Vertical legs with nylon adjustable feet. A Garbage chute is provided on LHS & a glass is fitted on the D.L.T.		2	
18	tiers	All shelves are made of 18 swg SS: 304 on 4 nos round/square legs with adjustable bullet feet. All the shelves are having 'C' Channel through to accommodate maximum load bearing ability		10	
19	Clean Dish LandingTable	Top 16 swg S.S304 sheet on MS Angle frame work duly rust proof painted & stud welded on SS. Tubular/square legs with adjustable bullet feet. Also fitted with SS slide out beneath to hold the plate/glass racks of 500 x 500 mm	1500x600x850	2	
20		Structure made of SS-304 square pipe $25x25$ frame work. Top & sink made of 16 swg and under shelf-made of 18 swg SS sheet. Vertical legs of SS round made of 16 swg 1.5 inch dia. With Nylon adjustable feet.	1800x600x850+150	2	
	Garbage Bin	Structure made of 16 swg thick SS-304 sheet, Angles, tubes/square channel with two tier 18 swg thick SS-304 shelves and Push cart handle and 4-swiveling wheels.	900x600x900	4	
22	Pot Rack- 4shelves	The heavy duty 4 tiers rack are made of S.S-304 square pipe (38mm & 25mm) and duly welded with 4 nos. uprights on nylone adjustable feet for uneven floor.	1200X600X1650	2	
		SS sheet. Vertical legs of SS round made of 16 swg 1.5 inch dia. With Nylon adjustable feet.	1500x750x850+150	2	
24		Top of 16 swg S.S-304 sheet on MS Angle 25x25mm frame work duly rust proof painted on Structure made of S.S-304 square/Tubular pipe. Under shelf made of 18 swg S.S-304 sheet. Vertical legs of S.S-304 round pipe of 16 swg. 1.5" dia with nylon adjustable feet. The top is fitted with stud welded bolts with the frame for sturdy and stronger grip.	1200x600x850	2	
25		With asynchronous Single phase, heavy duty and quiet motor. Stainless steel bowl and filter grid rubber. Aluminium casting and stainless steel construction bowl sustainer. Multipurpose combi machine; drink mixer, citreous juicer, blender. Separate motors for each function.		1	
26	Oven (Electrical)	Double Deck and Double walled mineral wool insulated body will have 18 swg. SS-304 sheet in front and doubly coated heat resistant MS sheet inside and MS plate on base. Fitted with 6 kw heating element with auto temp. controller and indicating lamps. The front opening insulated door is fitted with see through toughened glass and illumination in side to watch the proceedings with on/off switch. The entire oven is mounted on heavy duty SS legs on castor wheels. Also fitted with heat exracting duct behind to cool out after the operation.	40 ltrs.	1	
		Triple walled mineral wool insulated all SS sheet body on SS legs with adjustable bullet feet. The outer most wall and the second wall is mineral wool insulated and the other wall water proof and fitted with valet, over flow valves and water level indicator. Also fitted with 3.0 kw immersion type heating element with auto temperature controller and indicating lamps and a heavy duty gun metal faucet. A top opening lid with insulated handle is fitted. Also fitted with two nos, insulated handles on either sides to carry.	50 ltrs.	1	
28		Top of 16 swg. SS Sheet on M.S Angle frame work duly reust proof painted on SS Tubular/ Square legs with adjustable bullet feet for uneven floors. Fitted with United/Sarna make heavy duty burner with pilor lamps with individual control valves and geavy duty cast iron pan support. Also fitted with drip tran and a bottom shelf.	48"x24"x34"	2	
29		Complete frame work 20/22swg. Complete joints are air tight insulated weather proof mechanically painted on the Upper surface. S.S-304 filters-island type.	3000x900x600	1	
		Structure made of SS-304 square pipe 25x25 frame work. Top & sink made of 16 swg and under shelf made of 18 swg SS sheet. Vertical legs of SS round made of 16 swg 1.5 inch dia. With Nylon adjustable feet. Top of 18swg S.S-304 Sheet and sides & inner wall covered with 20 swg S.S-304 Sheet and Puff insulated provided		2	
- 51	Refrigerator	top of 188wg 5.3-504 Sheet and sucs & mine wan (overeu wint 20 swg 5.3-504 Sheet and ruft instance provincer with two doors & two S.S-304 Wire mashed adjustable trays powered with heavy duty Emerson/Techumshah/Kirloskar/Equivalent make condensing unit with Auto temp. Controller and indicating lamp.	205040004050	£	

	m m 1		000 (00 000			
32		Structure made of S.S-304 Square/Tubular pipe and MS Angle 25x25mm frame work duly rust proof painted .Push	900x600x900	1		
	Trolley	cart handle. Two trays made of 18 swg S.S-304 sheet, Vertical legs of S.S-304 round pipe of 16 swg. 1.5" dia with				
		swiveling castor-4 Nos.				
33	Hot Food	Double walled insulated with glass wool. Inner side made of 18swg & outer side made of 20 swg as Stainless steel 304	900x600x900	6	6	
	Service Trolley	sheet with 4 no heavy duty Castor wheels (4"/6" dia) with 2 wheels locking arrangement and push cart type handle				
		constructed from ss pipe. Trolley has Immersion type 3Kw heating elements with auto temp. controller & indicating lamp				
		with temp. Indicator to keep 4 Nos round containers with lids to keep food hot vegetable and one rectangular for				
		container for to keep chappaties. Also fitted with one middle and bottom shelves with lockable door. Rubber cushion to				
		be fitted at the corners to prevent damage during transportation.				
34	Weighing Scale	Electronic weighing scales of standard make to weigh upto 200 kg. The certificate from Weights & Measures Dept. is to	200kg	1	1	
54	Electronic	be attached with the machine, duly certifying the serial no.	ZOOKS		·	
	Licetronic	be attached with the infaction, duty certaining the serial no.				
35	Storage Rack	All shelves are made of 18swg S.S-304 sheet on 4 nos round/square legs with adjustable bullet feet. All the shelves are	900 x 450 x1800	4	4	
	with 5 tiers for	having "C" channel through to accommodate maximum load bearing ability				
	Vegetable store					
36	Onian/ Potato	The entire bin is made of S.S. wire meshed body on heavy duty castor wheels. Fitted with top opening lid and the	900x600x750	3	3	
	Bin	inclined bottom to have a lockable door to extract.				
37	Cereal/Atta/Ma	The entire bin made of 18 swg S.S-304 sheet on tiny caster wheels & with top opening lid.	900x600x900	3	3	
٥,	ida Bin	and the second and easier mices as man op opening in		_		
38	Cold Room	Room size-	2500 x 2500 x 2400	1	 	
50	Cold Robin	Temperature -0 to 4 degree centigrade Insulation: Panels 60mm thick PU	2300 A 2300 A 2400	1	·	
	1					
	1	at 40-42kg density, PCGI exposed exterior 0.5mm thick sheet, PCGI exposed exterior 0.5mm thick sheet, PCGI interior				
		0.5mm thick sheet, floor interior and exterior of 0.5mm thick PCGI exposed sheet, Ceiling exterior PCGI, interior PCGI				
		Sheet 0.5mm.Vertical, Panels Joint with Cam lock coupling in Tongue & Groove arrangement. Thickness of PUF Panels				
		(for Wall, Ceiling & Floor)- 60mm. Wall & Ceiling panels Finish- Internal: SS 304 External: PCGI Galvanized Ironic				
		Sheet. Flooring- Kota stone by client. Density of Panels-40kg/cub.m No. of Doors- One for Main Room Type. of Doors-				
		Over Lapped or Flash Type Door Size-900mm x 1950mm. Accessories Included in the scope of Supply-1. Door Alarm				
		2. Lock Defeat mechanism 3. Light Inside the cold room. 4. Handle, Hinges & Locks. 5. Microprocessor based digital				
		control. Panels. 6. Panel Accessories & necessary Hardware. Technical Feature of PUF Panels, Doors, & Accessories:				
		Individual Panel is manufactured with closed cell Rigid Polyurethane foam, injected at high pressure, which secures the				
		bond with facing material to form a single piece construction. RPUF insulation is CFC free and has Zero ODP- Ozone				
		Depleting potential. Core density of 40kg / Cu.M Panel finish is designed to resist many chemicals including most				
		common cleaning agents. The panels have fire rating to BS.467 part 7, clause 1. Wall, floor & ceiling panels joined with				
		Tongue and groove mechanism with cam lock system. The compressor and condenser unit of Emerson/				
		Techumshah/Kirloskar make with Automatic temperature controller and temp. Indicator.				
39		All shelves are made of 18 swg SS: 304 on 4 nos round/square legs with adjustable bullet feet. All the shelves are having	900x450x1800	6	6	
	tiers	'C' Channel through to accommodate maximum load bearing ability				
40	Storage Rack	All shelves are made of 18 swg SS: 304 on 4 nos round/square legs with adjustable bullet feet. All the shelves are having	800x450x1200	3	3	
	4tiers	'C' Channel through to accommodate maximum load bearing ability				
	<u> </u>					
41		LPG BANK				
		LI O DAIN				
	LPG Bank		1 Lot	1 lot	ot	
	1	6+6 (One set working another set standby) LPG Cylinder Bank of 14.2 Kg each LPG cylinder with :Class 'C' seamless				
	1	steel pipe conforming to IS:1239 (Latest version) with Pressure Gauges (0-15 PSIG & 0-5PSIG, dial type). Pressure				
	1	reducing stations complete with Flanges & accessories and Isolation valves having ball valves of approved makes with				
	1	LPG installation certificate having carbon steel body, SS ball and PTFE seat, Laboratory tap and all other fittings such as				
	1					
	1	tees, reducers, unions, elbows. Steel Grilled cage of area 12 ft x 4ft.with lockable door for keeping 6 + 6 Cylinder Bank.				
		Complete as per technical specification				
42	Insectocutor	Twin tube Insectocutor/s shall be provided at suitable locations.	Branded.	3	3	
	 					
	1					
43	Turnkey	As per Technical Specification	Lot	1	1	
7.7						
	1	SUB TOTAL Rs.				
			1			

	Part-II						
Item No.	Description 2	Unit 3	Qty 4	Unit Rate In Rs (in Figure) 5	Unit Rate in Rs (in Words) 6	Amount (Rs.) (In Figure)	
1.0	Comprehensive Maintenance Charges for the complete Kitchen appliances including spares, repair or replacement defective equipments/parts, tolls, tackles, accessories, consumables, labour charges etc. complete in all respect aft completion of Defect Liability Period as per the contract.						
	Ist Year	Job	1				
	2nd Year	Job	1				
	3rd Year SUB TOTAL Re	Job	1				
	SUMMARY OF RATES QUOTED						
1	TOTAL (PART-I)						
2	TOTAL (PART-II)						
Grand Total A	Amount (PART - I + PART - II) (in Figures) :-						
	In words: Rupees						

Signature of Bidder Name of Bidder Date Seal of the Bidder

- The above format of Bill of Quantity(BOQ) should be <u>neatly hand written</u>. The BOQ in any other format other
 than the aboveformat or typed written shall be rejected.
 The above quoted rates will be inclusive of all taxes, duties and other charges.

- 4 Cost of CMC will be added for ranking purpose

Note

- 5 Cutting and overwriting should be avoided. Correction should be countersigned always.
- 6 Incase any error between Unit rate in figure and unit rate in words, the unit rate in words shall be cosidered